RGBWW-Z RGB+CCT LED CONTROLLER

Control RGB+CCT LED Strip



PRODUCT PARAMETERS



PRODUCT NAME RGB+CCT LED Controller (Zigbee 3.0)	MODEL NO. RGBWW-Z
INPUT VOLTAGE DC12V-24V	OUTPUT 6A/Channel
TOATAL OUTPUT Max 12A	APPLICATION Control RGB+CCT LED Strip

PRODUCT DETAILS

01

POWER CONNECTOR

Input Voltage
DC12V-DC24V



02

LIGHT STRIP INTERFACE

Output Voltage
DC12V-DC24V

03

PREFERRED MATERIALS

Classic PC material
high quality



WIRING DIAGRAM



TUYA SMART APP CONTROL

- Millions of colors to choose
- Support music rhythm
- Color temperature 2700K/6500K
- Smartphone APP control
- Dim brightness/ Saturation
- Support third party voice control
- Device sharing
- Group control
- Scene customization
- Timing setting



APP CONTROL



APP CONTROL INSTRUCTION

1.Download [Tuya Smart] APP

2.Click " Register " button to create account

3.Log in directly if you already had account.

(Search for [Tuya Smart] in Apple / Google store or scan the QR code to download the app.)

STEPS FOR USAGE



1.POWER YOUR LIGHT SOURCES
Please connect the light strip controller, adapter and plug in the power.Switching the right mode.

2.SET UP YOUR BRIDGE
Plug in your bridge and it will automatically power up.Connect it to your router using the network cable provided.

3.DOWNLOAD THE GATEWAY APP
Start the device searching.It could take a few seconds to find the device, power off/on or make a reset.

4.COMPLETE THE SETUP AND CONTROL THE LIGHTS
You can control the light color,color temperature and brightness.

SUPPORT THIRD PARTY VOICE CONTROL

Need to be equipped with ZigBee 3.0 gateway,which can control ON/OFF brightness,colors,etc through voice.

It can enter into Philips Hue,IKEA TRADFRI,AMAZON Echo Plus(2nd Gen) Echo(4th Gen),Echo Studio,Echo show5 Gen)clarivision zigbee 3.0 gateway

CONNECT TO TUYA ZIGBEE GATEWAY

You must link the Tuya Zigbee 3.0 Gateway first to the smartphone,then add the zigbee controller to zigbee gateway for smartphone control.

1、How to connect zigbee gateway to smartphone,(Note:All Tuya Zigbee 3.0 gateway operation steps are the same,here we use our Zigbee 3.0 gateway for example)

First,power the zigbee gateway and long press the "SET" button until the red indicating lamp blinking.

Second, when the red indicating lamp blink, open the Tuya Smart APP and press"Add Device",it will discover the new device automatically, then Press"Add" to complete the linking.

2、Add the Zigbee controller to the linked zigbee gateway.

1.First,add subdevice

2.Second, power on/off 5 times to enter pairing mode

3.At last, Added successfully

CONNECT TO HUE GATEWAY

1.Add and Search light

2.Power ON/OFF 5 times till light blink to pair Bridge

APPLICATION SCENARIO